APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/781,990	02/13/2001	Antti Forstadius	4925-58	2033

7590   01/09/2006

Michael C. Stuart, Esq.
Cohen, Pontani,
Lieberman & Pavane
551 Fifth Avenue, Suite 1210
New York, NY 10176

EXAMINER
LEE, ANDREW CHUNG CHEUNG

ART UNIT	PAPER NUMBER
2664	

DATE MAILED: 01/09/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

PTO-90C (Rev. 10/03)

	Application No.	Applicant(s)
Office Action Summary	09/781,990	FORSTADIUS ET AL.
	Examiner	Art Unit
	Andrew C. Lee	2664

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE *3* MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on <u>03 October 2005</u>.

2a)☒ This action is **FINAL**.   2b)☐ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) *1-35 and 37-61* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) *1-35 and 37-61* is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All   b)☐ Some * c)☐ None of:

      1.☐ Certified copies of the priority documents have been received.

      2.☐ Certified copies of the priority documents have been received in Application No. _____.

      3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1)☒ Notice of References Cited (PTO-892)

2)☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3)☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____.

4)☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____ .

5)☐ Notice of Informal Patent Application (PTO-152)

6)☐ Other: _____.

DETAILED ACTION

Claim Rejections - 35 USC § 112

1.   The following is a quotation of the first paragraph of 35 U.S.C. 112:

> The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

2.   Claims 1, 13 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was **not described explicitly** and disclosed initially in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. The subject matters "one host computer operating as a host node" as disclosed in line 2, and "whereby transceiver nodes beyond transmission range of the at least one host node but within transmission range of one or more intermediate transceiver nodes accessible to said at least one host node and in wireless communication with said at least one host node become identified and accessible to said at least one host node relaying through said intermediate nodes" as disclosed in lines 16 – 21 of claim 1(page 2); "at least one host computer operating as a host" as disclosed in lines 2 – 3, and "whereby transceiver nodes beyond transmission range of the at least one host node but within transmission range of one or more intermediate transceiver nodes accessible to said at least one host node and in wireless communication with said at least one host node become identified and accessible to said at least one host node relaying through said intermediate nodes" as disclosed in lines 18 – 23 of claim 13 (page 4).

1.   The disclosure is objected to because of the following informalities:

- Regarding the amended claim 1, there is a type on item (a). The phase "and

   associating the at least one host with the value on n" is incorrect. It should be

   corrected as "and associating the at least one host with the value of n".

   Appropriate correction is required.

Claim Rejections - 35 USC § 102

2.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that

form the basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

3.   Claims 1, 13, 15, 46, 2, 4, 17, 19, 33, 3, 16, 18, 38, 5, 43, 50, 6, 20, 44, 51, 7, 21,

30, 8, 22, 9, 10, 11, 23, 24, 24, 31, 32, 34, 48, 49, 12, 14, 26 are rejected under 35

U.S.C. 102(e) as being anticipated by Plasson et al. (US 6795688 B1).

        Regarding Claims 1, 13, 15, 46, Plasson et al. disclose the limitation of method of

configuring a short range RF network (Fig. 1, column 8, lines 29 – 44; column 14, lines 47

– 50), the network comprising at least one host computer operating as a host node and at

least two wireless transceiver nodes, (Fig. 3A, column 7, lines 48 – 51; lines 63 – 67;

column 10, lines 33 – 40), each transceiver node having a controller (Fig. 1, elements 120

and 130; column 8, lines 23 - 28), a data store (Fig.2, element 210; column 9, lines 43 –

50), and at least one transceiver for communicating wirelessly with other host and

transceiver nodes (column 7, lines 63 – 67; Fig. 2, elements 190, column 9, lines 59 – 62),

each transceiver having a unique identifier (Fig. 4A, element 410; column 12, lines 38 –

40; column 15, lines 5 – 8), the method comprising the steps of: (a) the assigning a

predetermined value to a variable n and associating the at least one host with the value of

n (Fig. 4A, element 410; column 12, lines 38 – 40; column 15, lines 5 – 8); (b) paging all

other nodes from the node associated with a value of n (column 3, lines 43 – 51; column

8, lines 12 – 22; column 14, lines 26 – 52); (c) noting nodes which reply to paging and

associating them with a value of (n+1) (column 11, lines 34 – 36; column 17, lines 55 – 67;

Fig. 6, element 600, column 18, lines 47 – 51); (d) the making all nodes associated with

the value of n or with lower values unresponsive to paging (Fig. 6, column 19, lines 1 – 7);

(e) incrementing the value of n (Fig. 6, element 635; column 19, lines 1 – 3); and (f)

repeating steps (b) through (e) until no nodes reply to paging (Fig. 6, element 600),

Plasson et al. also disclose expressly whereby transceiver nodes beyond transmission

range of the at least one host node but within transmission range of one or more

intermediate transceiver nodes accessible to said at least one host node and in wireless

communication with said at least one host node become identified and accessible to said

at least one host node relaying through said intermediate nodes (Fig. 3A, Fig. 3B; column

10, lines 35 – 43; column 11, lines 6 – 11; lines 20 – 47;).

Regarding Claims 2, 4, 17, 19, 33, Plasson et al. the method, network of claimed wherein any host node is further a gateway to another network (column 8, lines 40 – 43; column 14, lines 47 – 50).

Regarding Claims 3, 16, 18, 38, Plasson et al. disclose the limitation of the method of claimed comprising step: (g) repeating steps (a) through (f) with a different host node selected as the host node (Fig. 5, element 500; Fig. 6 element 600; column 18, lines 41 – 67; column 19, lines 1 – 13).

Regarding Claims 5, 43, 50, Plasson et al. disclose the limitation of the method of claimed wherein the RF network is a short-range RF network (column 7, lines 48 – 53).

Regarding Claims 6, 20, 44, 51, Plasson et al. disclose the limitation of the method of claimed wherein the short-range RF network is a Bluetooth network (column 7, lines 48 – 53; lines 61 – 67; column 8, lines 6 – 7).

Regarding Claims 7, 21, 30, Plasson et al. disclose the limitation of the method of claimed wherein if a node comprising at least two transceivers (column 9, lines 59 – 67), the first one to answer paging is designated as a slave transceiver of the RF network (column 3, line 48 – 51) and least one of the other transceivers is designated as a master transceiver of the RF network (column 3, lines 43 – 45), and each transceiver designated as a master does not answer paging (column 3, line 45).

Regarding Claims 8, 22, Plasson et al. disclose the limitation of the method of claimed paging be performed by the master (column 3, lines 43 – 45).

Regarding Claims 9, 10, 11, 23, 24, 25, 31, 32, 34, 48, 49, Plasson et al. disclose the limitation of the method of claimed wherein a node further including a transceiver for

communication with wireless terminals (column 7, lines 61 – 67), whereby a wireless

terminal in transmission range of a node may communicate with another wireless terminal

in transmission range of a node (column 8, lines 6 – 22).

Regarding Claim 12, 14, 26, Plasson et al. disclose the limitation of the method of

claimed wherein each transceiver further has a password associated with it (column 12,

lines 38 – 40; column 15, lines 3 – 4), and wherein in step (c), passwords are included in

paging (column 15, lines 41 – 46); and a node does not reply to paging unless the

password included in paging matches the password associated with the transceiver

(column 15, lines 41 – 51, Table 1, Table 2, Table 3).

Claim Rejections - 35 USC § 103

4.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth
> in section 102 of this title, if the differences between the subject matter sought to be patented and the
> prior art are such that the subject matter as a whole would have been obvious at the time the invention
> was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability
> shall not be negatived by the manner in which the invention was made.

5.   Claims 27, 28, 35 are rejected under 35 U.S.C. 103(a) as being unpatentable over

Plasson et al. (US 6795688 B1) in view of Maletsky (US 6104279).

Regarding claims 27, 28, 35, Plasson et al. disclose the limitation of configuring an

access point based RF network, the network comprising a plurality of network nodes for

communicating with other nodes (Fig. 3A, column 10, lines 33 – 40). Plasson et al. does

not disclose expressly claimed wherein further each transceiver has associated with it a

portable machine-readable tag containing the transceiver's unique identifier; associated

with the network is a tag reader for reading the machine-readable tags; and step (a)

comprises substeps: (a1) presenting each tag to the tag reader; and (a2) transferring each

output of the tag reader to the data store of the control node. Maletsky discloses the

limitation of claimed wherein further each transceiver has associated with it a portable

machine-readable tag containing the transceiver's unique identifier (column 1, lines 59 –

60); associated with the network is a tag reader for reading the machine-readable tags

(column 1, lines 25 – 29); and step (a) comprises substeps: (al) presenting each tag to the

tag reader (column 1, lines 50 – 53); and (a2) transferring each output of the tag reader to

the data store of the control node (column 1, lines 53 – 56). It would have been obvious to

one of ordinary skill in the art at the time the invention was made to modify Plasson et al.

to include a claimed wherein further each transceiver has associated with it a portable

machine-readable tag containing the transceiver's unique identifier; associated with the

network is a tag reader for reading the machine-readable tags; and step (a) comprises

substeps: (al) presenting each tag to the tag reader; and (a2) transferring each output of

the tag reader to the data store of the control node such as that taught by Maletsky in

order to provide an RFID tag identification method that minimizes the complexity of the

design and implementation of the base station and the RFID comprising the system (as

suggested by Maletsky, column 2, lines 57 – 60).

6.   Claims 39, 37, 29, 40, 41, 42, 45, 47, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, are

rejected under 35 U.S.C. 103(a) as being unpatentable over Plasson et al. (US 6795688

B1) and Larsson et al. (US 6535498) as applied to claims 1, 13, 15, 46, 2, 4, 17, 19, 33, 3,

16, 18, 38, 5, 43, 50, 6, 20, 44, 51, 7, 21, 30, 8, 22, 9, 10, 11, 23, 24, 24, 31, 32, 34, 48,

49, 12, 14, 26, 27, 28, 35 above, and further in view of Maletsky (US 6104279).

Regarding claims 39, 37, 29, 47, 52, 54, 55, 56, 57, 58, 59, 60, 61, Plasson et al.

disclose the limitation of a self-configuring RF network (Fig. 1, column 8, lines 29 – 44;

column 14, lines 47 – 50) comprising a plurality of nodes for communicating wirelessly

with other nodes of the RF network, wherein at least one of the nodes is selected as a

control node (Fig. 3A, column 10, lines 33 – 40), each node including a control logic (Fig.

1, elements 120, 130; column 8, lines 23 – 28); a data store connected to the control logic

(Fig. 2, element 210; column 9, lines 43 – 50); at least one transceiver connected to the

control logic and identified by a unique address for communicating wirelessly with other

nodes of the network (Fig. 4A, element 410; column 12, lines 38 – 40); a transceiver list

database connected to the data store for storing updateable information of all transceivers

of the RF network for network configuration (Fig. 4A, column 15, lines 5 – 20); and a

dynamic variable linked to the transceiver list database for indicating position of each node

in the RF network relative to the control node (column 19, lines 24 – 29); wherein: (a) a

transceiver of the control node pages other transceivers in its transceiver list (column 3,

lines 43 – 45); (b) a transceiver of the control node detects other nodes within its coverage

area according to response of said other transceivers to paging (column 8, lines 12 – 22);

(c) the control node's transceiver list is updated according to said response of said other

transceivers to paging (column 14, lines 47 – 52); (d) the control logic associates detected

transceivers' information in the control node's transceiver list with a current value of the

dynamic variable (column 14, lines 1 – 11); and (e) the control logic directs propagating

the updated contents of the control node's transceiver list to all detected nodes in the

network (column 13, lines 10 – 23); and (f) the control logic of each detected node directs

incrementing the dynamic variable (column 19, lines 6 – 7); (g) a transceiver of each node

pages other transceivers in its transceiver list; each node detects other nodes within the

coverage area of its transceiver according to response of said other transceivers to paging

(column 14, lines 26 – 40); (i) each node's control logic directs updating the node's

transceiver list according to response of said other transceivers to paging (column 13,

lines 10 – 23); (j) the node's control logic associates detected transceivers' information in

the node's transceiver list with a current value of the dynamic variable (column 19, lines 6

– 7); (k) the control logic directs propagating the updated contents of each node's

transceiver list to all detected nodes in the network (column 13, lines 10 – 23); and

functions (g) through (k) are repeated until all nodes of the network are detected (Fig. 6,

element 600, column 18, lines 37 – 67; column 19, lines 1 – 13); and Plasson et al. do not

disclose expressly wherein the control logic of each node computes an indication of

current load carried by the node; each node dynamically transmits its load indication at

least to nodes within its transmission range; and each node dynamically receives and

stores load indications received from other nodes. Larsson et al. disclose the limitation of

wherein the control logic of each node computes an indication of current load carried by

the node (Fig.6, column 2, lines 24 – 32); each node dynamically transmits its load

indication at least to nodes within its transmission range; and each node dynamically

receives and stores load indications received from other nodes (column 5, lines 5 – 14). It

would have been obvious to one of ordinary skill in the art at the time the invention was

made to modify Plasson et al. to include a claimed wherein the control logic of each node

computes an indication of current load carried by the node; each node dynamically

transmits its load indication at least to nodes within its transmission range; and each node

dynamically receives and stores load indications received from other nodes. such as that

taught by Larsson et al. in order to allow reactive ad-hoc routing protocols to determine

whether more optimal routes exist between the source node and the destination node (as

suggested by Larsson et al., column 3, lines 66 – 68). However, both Plasson et al. and

Larsson et al. fail to disclose wherein associated with each transceiver is a unique

password, provided with each transceiver is a machine-readable tag on which is recorded

the transceiver's unique address and password and associated with the control node is a

reader for reading unique addresses and passwords from the tags and storing them in a

first node's transceiver list. Maletsky discloses the limitation of wherein associated with

each transceiver is a unique password, provided with each transceiver is a

machine-readable tag on which is recorded the transceiver's unique address and

password and associated with the control node is a reader for reading unique addresses

and passwords from the tags and storing them in a first node's transceiver list (Fig. 1B,

column 3, lines 66 – 67; column 4, lines 1 – 18; lines 25 – 33; 44 – 47; column 5, lines 18

– 19). It would have been obvious to one of ordinary, skill in the art at the time the

invention was made to modify both Plasson et al. and Larsson et al. to include wherein

associated with each transceiver is a unique password, provided with each transceiver is

a machine-readable tag on which is recorded the transceiver's unique address and

password and associated with the control node is a reader for reading unique addresses

and passwords from the tags and storing them in a first node's transceiver list such as that

taught by Maletsky in order to order to provide an RFID tag identification method that

minimizes the complexity of the design and implementation of the base station and the

RFID comprising the system (as suggested by Maletsky, column 2, lines 57 – 60).

Regarding claims 40, 45, Plasson et al. disclose the limitation of a self-configuring

RF network (Fig. 1, column 8, lines 29 – 44; column 14, lines 47 – 50) comprising a

plurality of nodes for communicating wirelessly with other nodes of the RF network,

wherein at least one of the nodes is selected as a control node (Fig. 3A, column 10, lines

33 – 40). Plasson et al. do not disclose expressly the RF network of claimed wherein the

control logic of each node dynamically calculates routes for transmitting messages to the

first node including relays through other nodes for nodes not within transmission distance

of the control node. Larsson et al. disclose the limitation of the RF network of claimed

wherein the control logic of each node dynamically calculates routes for transmitting

messages to the first node including relays through other nodes for nodes not within

transmission distance of the control node (column 2, lines 1 – 21). It would have been

obvious to one of ordinary skill in the art at the time the invention was made to modify

Plasson et al. to include the RF network of claimed wherein the control logic of each node

dynamically calculates routes for transmitting messages to the first node including relays

through other nodes for nodes not within transmission distance of the control node such

as that taught by Larsson et al. in order to allow reactive ad-hoc routing protocols to

determine whether more optimal routes exist between the source node and the destination

node (as suggested by Larsson et al., column 3, lines 66 – 68).

Regarding claims 41, 53, Plasson et al. disclose the limitation of a self-configuring

RF network (Fig. 1, column 8, lines 29 – 44; column 14, lines 47 – 50) comprising a

plurality of nodes for communicating wirelessly with other nodes of the RF network,

wherein at least one of the nodes is selected as a control node (Fig. 3A, column 10, lines

33 – 40). Plasson et al. does not disclose expressly the RF network of claimed wherein a

node not within transmission distance of the control node selects routes to the first node

traversing the fewest other nodes. Larsson et al. discloses the limitation of the RF

network of claim 40 wherein a node not within transmission distance of the control node

selects routes to the first node traversing the fewest other nodes (Fig. 7, column 8, lines 6

– 12). It would have been obvious to one of ordinary skill in the art at the time the

invention was made to modify Plasson et al. to include the RF network of claimed wherein

a node not within transmission distance of the control node selects routes to the first node

traversing the fewest other nodes such as that taught by Larsson et al. in order to allow

reactive ad-hoc routing protocols to determine whether more optimal routes exist between

the source node and the destination node (as suggested by Larsson et al., column 3, lines

66 – 68).

Regarding claim 42, Plasson et al. discloses the limitation of a self-configuring RF

network (Fig. 1, column 8, lines 29 – 44; column 14, lines 47 – 50) comprising a plurality of

nodes for communicating wirelessly with other nodes of the RF network, wherein at least

one of the nodes is selected as a control node (Fig. 3A, column 10, lines 33 – 40).

Plasson et al. does not disclose expressly the RF network of claim 41 wherein if several

routes traverse the fewest other nodes, a route is selected which has traverses nodes

having least aggregate load indication. Larsson et al. discloses the limitation of the RF

network of claimed wherein if several routes traverse the fewest other nodes, a route is

selected which has traverses nodes having least aggregate load indication (column 5,

lines 5 – 22; column8, lines 6 –12). It would have been obvious to one of ordinary skill in

the art at the time the invention was made to modify Plasson et al. to include the RF

network of claimed wherein if several routes traverse the fewest other nodes, a route is

selected which has traverses nodes having least aggregate load indication such as that

taught by Larsson et al. in order to allow reactive ad-hoc routing protocols to determine

whether more optimal routes exist between the source node and the destination node (as

suggested by Larsson et al., column 3, lines 66 – 68).

Response to Arguments

7.   Applicant's arguments filed 10/03/2005 with respect to claims 1 – 35, 37 – 61 have

been fully considered but they are not persuasive. Regarding the remarks from the

applicant (page 19 – 20), there are some discrepancies from the remarks. The applicant

recited subject matter claimed the invention is directed to configuring a short range RF

network such as that a plurality of users with terminal devices (e.g. mobile phones) are

enabled to communicate with a host computer or with one another (see pg.10, lines 15 –

17 of the specification). The quoted lines number was incorrect. However, the subject

matter is not disclosed explicitly in the claims during the time of initial filing the claims. The

reference Plasson et al. also discloses the subject matter (see column 7, lines 48 – 51).

Regarding claims 1, 13, 46, Applicant argues reference Plasson do not disclose

transceiver nodes beyond transmission range of the at least one host node but within

transmission range of one or more intermediate transceiver nodes accessible to said at

least one host node and in wireless communication with said at least one host node

become identified and accessible to said at least one host node relaying through said

intermediate nodes. Examiner contends reference Plasson disclosed transceiver nodes

beyond transmission range of the at least one host node but within transmission range of

one or more intermediate transceiver nodes accessible to said at least one host node and

in wireless communication with said at least one host node become identified and

accessible to said at least one host node relaying through said intermediate nodes had

actually been interpreted in previous office action (see Fig. 3A, Fig. 3B; column 10, lines

35 – 43; column 11, lines 6 – 11; lines 20 – 47; column 12, lines 28 – 36).

Regarding claims 29, 39, 52, 55, Applicant argues reference Maletsky do not

disclose "associated with each transceiver is a unique password, provided with each

transceiver is a machine-readable tag on which is recorded the transceiver's unque

address and password and associated with the control node is a reader for reading unique

addresses and passwords from the tags and storing them in a first node's transceiver list".

Examiner contends reference Maletsky discloses "associated with each transceiver is a

unique password, provided with each transceiver is a machine-readable tag on which is

recorded the transceiver's unique address and password and associated with the control

node is a reader for reading unique addresses and passwords from the tags and storing

them in a first node's transceiver list" had been interpreted in previous office action (see

Fig. 1B, column 3, lines 66 – 67; column 4, lines 1 – 18; lines 25 – 33; 44 – 47; column 5,

lines 18 – 19).

Conclusion

8.   The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure.

   • Ciotti, Jr. et al. US 6421731 B1 discloses method for routing data packets

      among the nodes whereby each of the nodes carries out the steps of

      maintaining a list of nodes which are reachable through the node based on

      advertisements received from other nodes.

   • Meier et al. US 6826165 B1 disclose communications between the host

      computer and the RF terminals is achieved by using the network of intermediate

      base stations to transmit the data.

9.   Applicant's amendment necessitated the new ground(s) of rejection presented in

this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a).

Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within TWO

MONTHS of the mailing date of this final action and the advisory action is not mailed until

after the end of the THREE-MONTH shortened statutory period, then the shortened

statutory period will expire on the date the advisory action is mailed, and any extension

fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory

action. In no event, however, will the statutory period for reply expire later than SIX

MONTHS from the date of this final action.

10.   Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Andrew C. Lee whose telephone number is (571) 272-

3131. The examiner can normally be reached on Monday through Friday from 8:30am -

5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Wellington Chin can be reached on (571) 272-3134. The fax phone number

for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published

applications may be obtained from either Private PAIR or Public PAIR. Status information

for unpublished applications is available through Private PAIR only. For more information

about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on

access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-

217-9197 (toll-free).

Ajit Patel
Primary Examiner

ACL   Dec 27, 2005